




Technical Data Sheet Art. No. 1368

AGE

Alkali-free stripping agent
removes graffiti and paints



For use in-
doors and
outdoors



Working
temperature
 $\geq +5\text{ °C}$



Brush, roller, low
pressure spray-
ing



Application
rate in total



Store frost-free
and cool,
protected from
moisture in
closed con-
tainers



Shelf-life

Range of use

Remmers AGE removes disper-
sion, pure acrylate and spirit var-
nishes, polishes as well as graffiti
from wood surfaces, metals and
mineral substrates.

Property profile

Remmers AGE is a water emulsifi-
able cleaning product in paste
form. It has a long action time
which allows deeper lying paint
remains and layers of varnish to be
reliably removed.

- N-methyl-pyrrolidon-free
- No chlorinated hydrocarbons
- Listed in the BAST list of
tested anti-graffiti systems,

Directions

Apply the material generously but
evenly with a brush or roller (no
plastic bristles) or airless equip-
ment and allow to act.

The stripper is removed with a
filling knife or a high pressure
cleaner.

The stripping effect depends on
the substrate, the material to be

Characteristic data of the product

Characteristic data of the product in the packaged state:

Density: 1.05 kg/l
pH value (20 °C): approx. 8.5 at 10 g/l water

stripped, ambient climate and
thickness of the layer applied.

The reaction time can be in-
creased by covering with a thin
plastic sheet.

Notes

A sufficiently large trial area should
always be set up to test compatibil-
ity with the substrate, its suitability
and to determine application rates.

When working indoors, make sure
there is good ventilation and ob-
serve job safety rules.

Observe legal provisions for lead-
ing into the sewage system and/or
disposing of the product mixed
with the removed paint. Notes

Protect adjacent surfaces, espe-
cially glass, wood, metal, etc. by
covering. Plants and trees should
also be protected.

A sufficient waiting time must be

observed if subsequent impregna-
tion is to be carried out.

Wear protective gloves, face pro-
tection and protective clothing
when applying and rinsing with a
high pressure cleaner.

Tools, cleaning

Scrub brush, application brushes,
lambskin roller, high pressure
cleaning equipment. Clean tools
with water after use.

Packaging, application rate, shelf-life

Packaging

0.75 l, 5 l and 25 l tin containers

Application rate

Approx. 300 - 500 g/m² depending
on type and layer thickness of the
respective old coating or graffiti

Shelf-life

At least 12 months in closed con-
tainers stored cool but frost-free.

At least 12 months in closed containers stored cool but frost-free.

Collection + disposal of rinsing water

Cleaner residue and rinsing water that contains the active ingredients of the product may not be led to the sewer system until they have been neutralised.

The pH value of the neutralised water should range between 7 and 9.

Observe the notes given in regulations on sewage and waste, Work Sheet A 115 DK 628.241 (083) + 628.543.

Gather rinsing water and dispose at a collection point or through the sewage system according to local regulations. Notes in the Work Sheet on "Waste and sewage from the cleaning and layer removal from facades".

Safety, ecology, disposal

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet.

Personal protective equipment is required for spraying procedures. Use respiratory protection with a combination filter at least A/P2 (made by e.g. Dräger). For suitable protective gloves, see Safety Data Sheet. Wear closed work clothes.



The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

1368 AGE_11.16

The logo for Remmers features a red stylized roof icon above the word 'remmers' in a bold, blue, sans-serif font.

Remmers (UK) Limited Crawley
United Kingdom
Tel: +44 (0) 1293 594 010
Fax: +44 (0) 1293 594 037
www.remmers.co.uk