



Product Data Sheet



Water and dirt repellent, vapor-regulating facade impregnation.

- Universally applicable
- Can be used on pre-impregnated surfaces

Product properties

- weber.klin hamoline ensures perfect water repellency and vapor regulating.
- Can be used on both dry and (preferably) damp surface.
- Invisible and dirt repellent.
- Can be applied to any silicate surfaces, such as concrete, concrete block, limestone, brick and cement plaster.
- weber.klin hamoline can be applied over previously impregnated surfaces.
- weber.klin hamoline with synthetic paint paintable, anti-fouling, lime retirement and reduces frost damage to stone and mortar. It is also resistant to alkali and acid (acid rain has no adverse effect).

Packaging

Tin à 5 and 10 liters.

Application

- Universally applicable
- Can be used on pre-impregnated surfaces
- At least 10 years effective
- Vapour Regulating





Product Data Sheet



Colour

Transparent.

Tools

Low pressure sprayer, white spirit and gloves.

Application rate

For a lasting effect should be applied at least 0.5 liters per sqm. With very absorbent substrates consumption can be up to 1 liter per square meter. 10 liters accounts for +/- 16 m and 5 liters for +/- 8 m² depending on application and surface.

Dosage

weber.klin hamoline is ready to use.

Preparation

- Preferably apply on a slightly damp surface.
- weber.klin hamoline must be applied pure, do not mix with water or other means.
- Wipe the surface clean or brush the surface.
- Repair any damage to jointing (add and / or plaster must be at least two weeks old).
- windows and window covering and flooring, roofing felt and cover plants.

Application

- Shake the container before use.
- Apply weber.klin hamoline preferably pouring in. Working from the top down and pour wet-on-wet over the solvent front. Just make sure this happens plentiful.

Cleaning

- Remove any splashes on glass, tools, plastic or paint directly with turpentine. Dried weber.klin hamoline can not be removed.

Technical composition

- Composition: solution of silicone resin having alkoxy groups.
- Do not apply below 5 ° C.
- Density: 0.8 kg / ltr.

Shelf life

2 years after production date if kept dry and frost-free in the closed original packaging.

Notice

- Repeated exposure may cause skin dryness or cracking.
- Vapour / spray inhalation.
- Avoid contact with skin.
- May cause lung damage if swallowed: when swallowed, do not induce vomiting; seek medical advice immediately and show the package.

